

PURITY SERIES-CI (VL-7503)



Diffused LED Bollard light for LED lamps (E-27)

Mounting heights	231mm
Installation anchor size	S.T.S Ø9 X □120mm or Ø9 X △70mm
Luminous flux [lm]	470[lm] - 1,250[lm]
Protection Class	IP67
Certification	KS C 7713 _ LED 경관등



Description


가장 기본적인 형태의 PURITY-CI는 간접조명의 효과를 연출 할 수 있도록 디자인된 조명기구이다. 유백색 폴리 카보네이트 커버를 통해 투사되는 빛의 특성과 심플한 외형은 기존 조명기구들의 디자인에서 크게 벗어나지 않으면서 포인트를 주어 조명디자이너의 욕구를 충분히 충족 시킬 수 있는 제품이다. 기존 광원 EL 20W를 LED 9W로 대체가 가능하여 55%의 에너지 절약 효과가 있다. 또한 베이스가 같은 다양한 램프와 호환이 가능하며, 전원공급 장치가 내장되어 편리하게 설치 및 유지보수가 가능한 제품이다.



CLASS I 2.95kg

MODEL	CODE NO.	LAMP	BASE	INPUT	lm/cd
	7503-L7	LED BULB 7W	E-27	AC 220V	470[lm]
PURITY-CI 퓨리티-씨아이	7503-L9	LED BULB 9W	E-27	AC 220V	806[lm]
	7503-L11	LED PAR30 11W	E-27	AC 220V	860[lm]
	7503-L15	LED PAR30 15W	E-27	AC 220V	1,250[lm]

- Material :** Body_ aluminum die casting. Diffuser_ 30mm toughened anti UV satin polycarbonate. Decoration_ steel plate. (direct current electroplating) Pole_ post extruding aluminum pipe. Lamp holder_ steel plate. (direct current electroplating) Gasket and seals_ silicone rubber. Fixings_ stainless steel screws.
- Vents :** Waterproof protective lamp vent (IP67)
- Finishing :** Mechanical and chemical anticorrosion treatment; AKZONOBEL, Polyester, UV resistant, exterior paint system, thermally cured at 200 °C
- Adjustment :** Fixed lighting fixture
- Paint Color :** Dark gray painted (Standard) / Another paint color on request
- Power :** Electronic power supply unite included
- Input Voltage :** AC 220~240V 60Hz
- Options :** Cable lengths on request
Standard anchor base size (Ø9 X □120mm)
Option anchor (Ø9 X △70mm) on request



_Anchor detail



Energy Saving
55%
LED bulb 9W vs EL 20W