

EDGE SERIES-OPEN (VL-7010)


Shielded LED Bollard light for waterproof type LED PCB module

Mounting heights	575mm - 900mm
Installation anchor size	S.T.S Ø9 X □170mm
Luminous flux [lm]	956[lm] - 1,755[lm]
Color temperature	3,200°K / 5,500 °K / 6,500 °K
Protection Class	IP67
Certification	KS C 7713 _ LED 경관등



Description

조명기구 측면을 사선으로 디자인한 EDGE는 심플하면서도 세련된 마감처리가 돋보이며, 방수형 모듈(IP67)을 헤드에 부착하는 방식으로 기존 광원 MH 35W를 55% 에너지 절약을 하면서 LED MODULE 16W로 대체가 가능한 제품이다. 여러 공간에 부합될 수 있도록 다양한 크기를 갖추고 있으며, 긴 수명과 전력소비 절감과 녹색성장에 부흥하는 저탄소 무공해 물질의 친환경 조명기구이다. 또한 전원공급장치가 내장되어 편리하게 설치 및 유지보수가 가능한 제품이다.



CLASS I 15.4kg

MODEL	CODE NO.	LAMP	BASE	INPUT	lm/cd
EDGE OPEN	7010-M10	LED MODULE 10W	LED ENGINE	AC 220V	956[lm]
엣지 오픈	7010-M16	LED MODULE 16W	LED ENGINE	AC 220V	1,755[lm]

- Material :** Body_ steel pipe.(direct current electroplating) Diffuser_ 5mm toughened anti UV clear polycarbonate. Cover frame_ steel plate.(direct current electroplating) Heat sink_ post extruding aluminum. Converter holder_ steel plate. (direct current electroplating) Pole_ steel pipe. (direct current electroplating) Gasket and seals_ silicone rubber. Fixings_ stainless steel screws.
- Finishing :** Mechanical and chemical anticorrosion treatment; AKZONOBEL, Polyester, UV resistant, exterior paint system, thermally cured at 200 °C
- Adjustment :** Fixed lighting fixture
- Power :** Electronic power supply unite included
- Input Voltage :** AC 220~240V 60Hz
- Options :** Cable lengths on request
- Paint Color :** Dark gray painted (Standard) / Another paint color on request



Energy Saving
55%
LED 16W vs Metal halide 35W