

SMILE SERIES-CLOSE (VL-7001)



Shielded LED Bollard light for LED MR16 (GU5.3)

Mounting heights	479mm - 867mm
Installation anchor size	S.T.S Ø9 X □120mm or Ø9 X △70mm
Luminous flux [lm]	470[lm] - 480[lm]
Protection Class	IP67
Certification	KS C 7713 (LED 경관등)



Description


웃음을 지을 때 나타나는 입 모양을 형상화하여 디자인한 SMILE은 보는 이들의 입가에 미소를 선사할 수 있는 조명기구이다. 온화하면서도 안정적인 빛의 효과를 느낄 수 있도록 유백색 폴리카보네이트를 통해 상향으로 빛이 분포된다. 그리고 공간감과 하부 조도확보를 위한 간접조명 형태의 하향식 빛은 시민들의 휴식공간의 즐거운 등불이 되어 줄 것이다. 또한 LED, 전원공급장치가 내장되어 편리하게 설치 및 유지보수가 가능하며, LED 랩프 사용으로 어디서든 쉽게 구매 할 수 있어 유지관리가 수월한 제품이다.



CLASSIFIED BY INDUSTRIAL DESIGNER 4.52kg

MODEL	CODE NO.	LAMP	BASE	INPUT	lm/cd
SMILE-CLOSE (스마일-크로스)	7001-L5.6	LED MR16 5.6W	GU5.3	AC 220V	480[lm]
	7001-L8	LED MR16 8W	GU5.3	AC 220V	470[lm]

- Materials :** Body_ aluminum die casting. Diffuser_ 30mm toughened anti UV satin polycarbonate + 6mm toughened clear polycarbonate. Pole_ post extruding aluminum pipe. Converter & led & lamp holder_ steel plate. (direct current electroplating) Gasket and seals_ silicone rubber. Fixings_ stainless steel screws.
- Vents :** Waterproof protective lamp vent (IP67)
- Finishing :** Mechanical and chemical anti-corrosion treatment; AKZONOBEL, Polyester, UV resistant, exterior paint system, thermally cured at 200 °C
- Adjustment :** Fixed lighting fixture
- Paint Color :** Dark gray painted (Standard) / Another paint color on request
- Power :** Electronic power supply unite included
- Input Voltage :** AC 220~240V 60Hz
- Option :** Cable lengths on request
Standard anchor base size (Ø9 X □120mm)
Option anchor (Ø9 X △70mm) on request



_Anchor detail



Energy Saving
89%
LED MR 5.6W vs Halogen MR 50W