

STAIR (VL-7021)



Shielded LED Bollard light for LED PCB type

Mounting heights	905mm
Installation anchor size	S.T.S Ø9 X □120mm or Ø9 X △70mm
Luminous flux [lm]	960[lm] - 1,600[lm]
Protection Class	IP65
Certification	KS C 7713 _ LED 경관등



Description

계단층을 모티브로 상단 장식을 디자인한 STAIR은 하부 투사 방식의 조명기구이다. 광원이 드러나지 않는 간접 조명 방식이며, 조경, 공원, 주거지역 등 시민들의 휴식공간에 적용하기에 탁월한 심플한 디자인이 특징적인 제품이다. 또한 기존 조명기구들의 디자인에서 크게 벗어나지 않으면서 포인트를 주어 조명디자이너의 욕구를 충분히 충족시킬 수 있는 제품이다.



CLASS I 6.55kg

MODEL	CODE NO.	LAMP	BASE	INPUT	lm/cd
STAIR	7021-P12	LED 12W	PCB	AC 220V	960[lm]
스태어	7021-P20	LED 20W	PCB	AC 220V	1,600[lm]

Material : Body_ aluminum die casting. Diffuser_ 3mm toughened anti UV PET. Decoration_ aluminum die casting. Top cover_ aluminum die casting. Reflector_ steel specular. Converter holder_ steel plate. (direct current electroplating)
Pole_ post extruding aluminum pipe. Gasket and seals_ silicone rubber. Fixings_ stainless steel screws.

Finishing : Mechanical and chemical anticorrosion treatment; AKZONOBEL, Polyester, UV resistant, exterior paint system, thermally cured at 200 °C

Adjustment : Fixed lighting fixture


Paint Color : Dark gray painted (Standard) / Another paint color on request

Power : Electronic power supply unite included

Input Voltage : AC 220~240V 60Hz

Options : Cable lengths on request

Standard anchor base size (Ø9 X □120mm)
 Option anchor (Ø9 X △70mm) on request



_Anchor detail



Energy Saving
43%
 LED 20W vs Metal halide 35W