

## LUCE (VL-3010)


Impact-resistant bracket lights for LED PCB type

Beam angle	Symmetrical
Luminous flux [lm]	1,020[lm] - 2,040 [lm]
Protection Class	IP65
Certification	KS C 7713 (LED 경관등)




### Description

유백색 커버를 통해 발산되는 온온한 빛을 통해 안락함을 느낄 수 있는 LUCE는 건축물, 조경, 공원, 시민의 휴식공간에 배치 및 설계되어 아름다운 경관조명 이미지를 연출할 수 있는 조명기구이다. 단조로운 외벽이나 기둥에 온화함을 느낄 수 있는 최적의 조명기구이며, 기존 광원 EL 23W 를 LED 12W로 대체가 가능하여 48%의 에너지 절약 효과가 있다. 또한 친환경적인 직사광선으로 피사체에 대한 훼손이 발생하지 않으므로 녹색성장에 부응하는 저탄소 무공해 물질의 친환경 제품이다.



Energy Saving  
48%  
LED 12W vs EL 23W



CLASS 1 AND 2 FOR PEDESTAL

MODEL	CODE NO.	LAMP	BASE	INPUT	lm/cd
LUCE (루체)	3010-P12	LED 12W	PCB	AC 220V	1,020[lm]
	3010-P24	LED 24W	PCB	AC 220V	2,040[lm]

- Materials :** Body\_ aluminum die casting. Diffuser\_ 3mm toughened anti UV frosted (milky) polycarbonate. Cover frame\_ aluminum die casting. . Attach bracket\_ steel plate(selecting color powder painted). Gasket and seals\_ silicone rubber. Fixings\_ stainless steel screws.
- Finishing :** Mechanical and chemical anti-corrosion treatment; AKZONOBEL, Polyester, UV resistant, exterior paint system, thermally cured at 200 °C
- Adjustment :** Fixed lighting fixture
- Paint Color :** Dark gray painted (Standard) / Another paint color on request
- Power :** Electronic power supply unite included
- Input Voltage :** AC 220~240V 60Hz
- Option :** Cable lengths on request

