

SQUARE SERIES-30/50 (VL-1010)


Flood lights for waterproof type MONO LED PCB module

Beam angle	Symmetrical(10W Module) / Asymmetrical(16W Module)
Luminous flux [lm]	2,850[lm] - 4,700[lm]
Color temperature	3,200°K / 5,500 °K / 6,500 °K
Protection Class	IP65
Certification	KS C 7712 (LED 투광등기구)



Description

기존 LED 투광조명기구와 달리 대칭형, 비대칭형 빔각으로 아파트, 교량, 공원등에 다양한 연출이 가능한 제품으로 전원공급장치가 내장되어 편리하게 설치 및 유지보수가 가능하다. 긴 수명과 전력소비 절감으로 녹색 성장에 부응하는 저탄소 무공해 물질의 친환경 제품이다.




Energy Saving
57%
LED 30W vs Metal halide 70W



1010-P50

1010-P30



CLASS III

MODEL	CODE NO.	LAMP	BASE	INPUT	lm/cd
SQUARE	1010-P50	LED 50W	PCB	DC 24V	4,750[lm]
	1010-P30	LED 30W	PCB	DC 24V	2,850[lm]

- Materials :** Body_ aluminum die casting. Diffuser_ 8mm toughened anti UV clear polycarbonate. Cover frame_ aluminum die casting. Tilt gear_ aluminum die casting. Bracket_ stainless steel plate. Heat sink_ aluminum die casting. Gasket and seals_ silicone rubber. Fixings_ stainless steel screws.
- Finishing :** Mechanical and chemical anti-corrosion treatment; AKZONOBEL, Polyester, UV resistant, exterior paint system, thermally cured at 200 °C
- Adjustment :** Adjustable verticality 270° / horizontality 30°
- Paint Color :** Dark gray painted(Standard) / Another paint color on request
- Power :** Electronic power supply unite included
- Input Voltage :** DC 24V
- Control Gear :** Sub-controller included (Request on external sub-controller)
- Option :** Remote divers on request (Dimming, color change)
Cable lengths on request

